

DI Flanged Type Fittings



Description

With our wide and varied range of fittings in accordance with EN 545/ EN 598, we offer the most suitable solution for almost all applications, completed with our special fittings. Many of these products are manufactured according to relevant norms & certificates or according to customer requirement.

Our program includes the following flanged fittings from diameter DN 40 up to DN 1600 with pressure Rating PN 10/16 and PN 25

- Flanged spigots pipes with puddle flanges according to customer required length
- Double flanged pipes with puddle with boss and side flanged outlet
- Double flanged bends 11° – 90°
- Double flanged duck foot bends
- Double flanged bends 90°
- Double flanged Reducer(concentric & Eccentric)
- Tee (Equal & Unequal)
- Cross
- Studded Reducer Flange
- Blank flanges
- Adaption flange

Features

- ✓ Body : Ductile Iron
- ✓ Coating : Fusion bonded Epoxy 300 microns inside/ outside and cement lined inside & Bitumen coated outside
- ✓ Nominal pressure : PN 10/PN16/PN25 and PN 40 on request
- ✓ OVGW,KIWA,DVGW & WRAS approved
- ✓ Standrad flanges : EN 1092-2, PN10/PN16/PN25. PN 40 on request
- ✓ Special fittings are available on request(Nonstandard length)